


CVTC SERIES

Vapor Tight Fixture



DESIGN

The CVTC Series Vapor Tight Fixture is a totally enclosed and gasketed, wet location rated fluorescent fixture. They are suitable for indoor and outdoor applications, food processing, walk-in freezers, schools, dormitories, restrooms, or anywhere dust, moisture, or vandalism may be an issue.

ACCESSORIES

Order as separate line item

6' 16/3 CORD W/ 15A NEMA PLUG
 C1 (120V)
 C2 (277V)
 C4 (480V)


1/2" MYERS HUB MH

T8 EMERGENCY BALLAST
 EB5 (500 LUMEN)
 EB7 (700 LUMEN)
 EB14 (1400 LUMEN)
 EB30 (3000 LUMEN)


MOTION SENSOR WOC (120/277V)
 WOC1 (347/480V)

PHOTOMETRICS

IES INDOOR REPORT
 PHOTOMETRIC FILENAME : CVT232.IES
 POLAR GRAPH



IES INDOOR REPORT
 PHOTOMETRIC FILENAME : CVT254.IES
 POLAR GRAPH



Maximum Candela = 1128 Located At Horizontal Angle = 90, Vertical Angle = 27.5
 # 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
 # 2 - Horizontal Cone Through Vertical Angle (27.5) (Through Max. Cd.)

Maximum Candela = 2164 Located At Horizontal Angle = 90, Vertical Angle = 30
 # 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
 # 2 - Horizontal Cone Through Vertical Angle (30) (Through Max. Cd.)

ORDERING INFORMATION

Description	Part Number
1L 32W T8 120/277V	CVTC132D(A)
1L 54W T5HO 120/277V	CVTC154D(A)
1L TANDEM ¹ 32W T8 120/277V	CVTCT132D(A)
1L TANDEM ¹ 54W T5HO 120/277V	CVTCT154D(A)
2L 32W T8 120/277V	CVTC232D(A)
2L 54W T5HO 120/277V	CVTC254D(A)
2L TANDEM ¹ 32W T8 120/277V	CVTCT232D(A)
2L TANDEM ¹ 54W T5HO 120/277V	CVTCT254D(A)
3L 32W T8 120/277V	CVTC332D(A)
3L 54W T5HO 120/277V	CVTC354D(A)
3L TANDEM ¹ 32W T8 120/277V	CVTCT332D(A)
3L TANDEM ¹ 54W T5HO 120/277V	CVTCT354D(A)

Option Codes

- (A) Options
 Blank - None
 10RS - ≤10% THD, Rapid Start
 P - Program Start
 20 - ≤20% THD

MOUNTING

2 Sets of each mount must be ordered per fixture

(3)S HOOKS AND CHAIN SET 10JC

MOUNTING BRACKET COMES STANDARD WITH FIXTURE

TECHNICAL INFORMATION

Housing is constructed of gray reinforced fiberglass body and a high impact polycarbonate diffuser. Continuous gasketing is formed to housing to provide a seamless seal. Suitable for wet locations. Ballasts are solid state electronic. Ballasts and lamp holders are replaceable without removing from ceiling. All reflective surfaces are finished with a high reflectance, lighting fixture white polyester powder.

Notes: 1-The number of lamps referred to in the description is the number of lamps per cross section. There are two cross sections in a tandem fixture.