


DLE SERIES

Die-Cast LED Exit Sign



DESIGN

The DLE Series Die-Cast LED Exit Sign is a compact, low-profile design. Spec-grade curved faceplate. Ultra bright energy efficient LED technology with red or green LED's. Universal mounting canopy making for quick and easy installation. Easily removable chevron direction indicators.

ORDERING INFORMATION

Description	Part Number ¹
RED LTR, WHITE PANEL, WHITE HSG	DLER2WW(A) (B)
RED LTR, WHITE PANEL, BLACK HSG	DLER2WB(A) (B)
RED LTR, WHITE PANEL, ALUMINUM HSG	DLER2WA(A) (B)
RED LTR, BLACK PANEL, WHITE HSG	DLER2BW(A) (B)
RED LTR, BLACK PANEL, BLACK HSG	DLER2BB(A) (B)
RED LTR, BLACK PANEL, ALUMINUM HSG	DLER2BA(A) (B)
RED LTR, ALUM PANEL, WHITE HSG	DLER2AW(A) (B)
RED LTR, ALUM PANEL, BLACK HSG	DLER2AB(A) (B)
RED LTR, ALUM PANEL, ALUMINUM HSG	DLER2AA(A) (B)
GREEN LTR, WHITE PANEL, WHITE HSG	DLEG2WW(A) (B)
GREEN LTR, WHITE PANEL, BLACK HSG	DLEG2WB(A) (B)
GREEN LTR, WHITE PANEL, ALUMINUM HSG	DLEG2WA(A) (B)
GREEN LTR, BLACK PANEL, WHITE HSG	DLEG2BW(A) (B)
GREEN LTR, BLACK PANEL, BLACK HSG	DLEG2BB(A) (B)
GREEN LTR, BLACK PANEL, ALUMINUM HSG	DLEG2BA(A) (B)
GREEN LTR, ALUM PANEL, WHITE HSG	DLEG2AW(A) (B)
GREEN LTR, ALUM PANEL, BLACK HSG	DLEG2AB(A) (B)
GREEN LTR, ALUM PANEL, ALUMINUM HSG	DLEG2AA(A) (B)

Option Codes

(A) Battery

Blank - AC Only
B - Battery Back-Up

(B) Options

Blank - None
SD - Self Diagnostic
2C - Dual Circuit²

TECHNICAL INFORMATION

Fixture features a premium grade, extruded aluminum housing. Dual 120V/277V voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. Low Voltage Disconnect (LVD) prevents battery from deep discharge. Internal solid state transfer switch automatically connects the internal battery to LED board for minimum 90 minute emergency illumination (B¹ Model Only).

Notes: 1-"B" Model is a fixture ordered with the optional battery back-up.