


KDT5 SERIES

T5 Low-Profile Knock Down Strip



DESIGN

The KDT5 Low-Profile Knock Down Strip is designed as a high quality, efficient T5 strip light. It can be used in a number of general lighting applications such as in shallow coves, showcases, displays, and used for task lighting.

ACCESSORIES

Order as separate line item



6' 16/3 CORD W/ 15A
NEMA PLUG
C1 (120V)
C2 (277V)
C4 (480V)



WIRING HARNESS
WH34 (3 WIRE, 4')
WH44 (4 WIRE, 4')
WH54 (5 WIRE, 4')



T8 EMERGENCY BALLAST
EB5 (500 LUMEN)
EB7 (700 LUMEN)
EB14 (1400 LUMEN)
EB30 (3000 LUMEN)



MOTION SENSOR
WOC (120/277V)
WOC1 (347/480V)

ORDERING INFORMATION

Description	Part Number ¹
1L 14W T5 120/277V	KDT511424D (A)
1L 21W T5 120/277V	KDT512136D (A)
1L 24W T5HO 120/277V	KDT512424D (A)
1L 28W T5 120/277V	KDT512848D (A)
1L 39W T5HO 120/277V	KDT513936D (A)
1L 54W T5HO 120/277V	KDT515448D (A)
2L 14W T5 120/277V	KDT521424D (A)
2L 21W T5 120/277V	KDT522136D (A)
2L 24W T5HO 120/277V	KDT522424D (A)
2L 28W T5 120/277V	KDT522848D (A)
2L 39W T5HO 120/277V	KDT523936D (A)
2L 54W T5HO 120/277V	KDT525448D (A)

Option Codes

(A) Options

Blank - None
10RS - ≤10% THD, Rapid Start
P - Program Start
20 - ≤20% THD

MOUNTING

2 Sets of each mount must be ordered per fixture



(3)S HOOKS AND
CHAIN SET
10JC



TONG HANGER
THE (END MOUNT)
THS (SIDE MOUNT)



AIRCRAFT CABLE WITH
12" ARMS
G10 (10')
G12 (12')
G15 (15')

TECHNICAL INFORMATION

Fixture housing, lamp holder brackets, end sections, and channel cover are constructed of heavy gauge die-formed steel. ETL listed. Suitable for damp locations. Ballasts are T5 solid state electronic. Ballasts and lamp holders are replaceable without removing from ceiling. Can be mounted as single fixture or in a continuous row. All reflective surfaces are finished with a high reflectance, lighting fixture white polyester powder.