


NKDS SERIES

T8 Low-Profile Knock Down Strip



DESIGN

The NKDS Low-Profile Knock Down Strip is designed as a high quality, efficient T8 strip light. It can be used in a number of general lighting applications such as in shallow coves, showcases, displays, and used for task lighting.

ACCESSORIES

Order as separate line item

6' 16/3 CORD W/ 15A NEMA PLUG
 C1 (120V)
 C2 (277V)
 C4 (480V)



WIRING HARNESS
 WH34 (3 WIRE, 4')
 WH44 (4 WIRE, 4')
 WH54 (5 WIRE, 4')


T8 EMERGENCY BALLAST
 EB5 (500 LUMEN)
 EB7 (700 LUMEN)
 EB14 (1400 LUMEN)
 EB30 (3000 LUMEN)



MOTION SENSOR
 WOC (120/277V)
 WOC1 (347/480V)

PHOTOMETRICS

IES INDOOR REPORT
 PHOTOMETRIC FILENAME : NKDS132.IES
 POLAR GRAPH



Maximum Candela = 475 Located At Horizontal Angle = 0, Vertical Angle = 45
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
 # 2 - Horizontal Cone Through Vertical Angle (45) (Through Max. Cd.)

ORDERING INFORMATION

Description	Part Number
1L 17W T8 120/277V	NKDS1172D (A)
1L 25W T8 120/277V	NKDS1253D (A)
1L 28W T8 120/277V	NKDS128T84D (A)
1L 32W T8 120/277V	NKDS1324D (A)

Option Codes

- (A) Options
 Blank - None
 10RS - ≤10% THD, Rapid Start
 P - Program Start
 20 - ≤20% THD

MOUNTING

2 Sets of each mount must be ordered per fixture



(3)S HOOKS AND
 CHAIN SET
 10JC



TONG HANGER
 THE (END MOUNT)
 THS (SIDE MOUNT)



AIRCRAFT CABLE WITH
 12" ARMS
 G10 (10')
 G12 (12')
 G15 (15')

TECHNICAL INFORMATION

Fixture housing, lamp holder brackets, end sections, and channel cover are constructed of heavy gauge die-formed steel. ETL listed. Suitable for damp locations. Ballasts are T8 solid state electronic. Ballasts and lamp holders are replaceable without removing from ceiling. Can be mounted as single fixture or in a continuous row. All reflective surfaces are finished with a high reflectance, lighting fixture white polyester powder.