



Catalog Number	
Project	Type

Features & Specifications

Application

This fixture is an excellent choice for commercial industrial and retail applications such as storage/utility areas, shops, task and general area lighting.

Features

Optimized for T8 or T5 lamp performance. Premium housing crimped along sides for extra rigidity and straight alignment. Features pressure lock lamp holders. Accepts optional plug-in wiring feature for continuous row installation. Alignment couplers furnished for continuous row installation. Can be surface or pendant mounted, individual or in rows. Numerous KO's for easy installation.

Construction

Fixture housing, lamp holder brackets, end sections and channel over constructed of heavy gauge die-formed steel. Crimped along sides for extra rigidity and straight alignment.

Electrical System

ETL listed. Suitable for damp locations. Damp location emergency pack must be specified separately. Ballasts are solid-state electronic. Ballasts and lamp holders are replaceable without removing from ceiling. Discrete voltage must be specified for emergency pack options when wired with flex.

Finish


All reflective surfaces are finished with a high reflectance, lighting fixture white polyester powder.

NS SERIES NARROW STRIP





DIMENSIONS

Asymmetrical Reflector



Symmetrical Reflector



Made in the USA

Please contact your Horizon Sales Representative for more information.

All dimensions subject to change without notice.

Ordering Nomenclature

Ex: (Narrow Strip, 2, F32T8, 4', Multi-Volt =NS232D)

--	--	--	--	--	--	--

SERIES	NUMBER OF LAMPS	WATTAGE	REFLECTOR	VOLTAGE	BALLAST FACTOR	OPTIONS
NS NSA (Aluminum)	1	14 - 14W T5, 22"	BLANK - None	D - Multi-Volt		10RS - ≤10% THD, Rapid Start
	2 (Per cross section)	17 - 17W T8, 24"	SS - Solid	1 - 120V	BLANK - Normal	P - Program Start
		21 - 21W, T5, 34"	Symmetrical	2 - 277V	H - High	20 - ≤20% THD
		24 - 24W T5HO, 22"	US - Uplight	3 - 347V	L - Low	EB5 - 500 Lumen T8 Emergency Ballast
		25 - 25W, T8, 36"	Symmetrical	4 - 480V		EB7 - 700 Lumen T8 Emergency Ballast
		28T5 - 28W T5, 46"	SA - Solid			EB14 - 1400 Lumen T8 Emergency Ballast
		28T8 - 28W T8, 48"	Asymmetrical			EB30 - 3000 Lumen T8 Emergency Ballast
		32 - 32W T8, 48"	UA - Uplight			EB5T5 - 500 Lumen T5 Emergency Ballast
		39 - 39W, T5HO, 34"	Asymmetrical			EB7T5 - 700 Lumen T5 Emergency Ballast
		48HO - 60W 800mA, 48"		*Multi-Volt is 120/277V		EB14T5 - 1400 Lumen T5 Emergency Ballast
		54 - 54W T5HO, 46"				FBF - Fast-Blow Fuse
		59 - 59W T8, 96"				SBF - Slow-Blow Fuse
		86 - 86W T8HO, 96"				AC63 - 6', 3/8" dia., Armored Flex Cable
WH54 - Wiring Harness 5-Wire 4-Foot		THE - Tong Hanger, End Mount (2)				SJ6 - 6', 3/8" dia., 16/3 SJ Cord
WH38 - Wiring Harness 3-Wire 8-Foot		THS - Tong Hanger, Side Mount (2)				SJ10 - 10', 3/8" dia., 16/3 SJ Cord
WH48 - Wiring Harness 4-Wire 8-Foot		G10 - 10' Aircraft Cable w/ 12" Arms (2)				SJ15 - 15', 3/8" dia., 16/3 SJ Cord
WH58 - Wiring Harness 5-Wire 8-Foot		G15 - 15' Aircraft Cable w/ 12" Arms (2)				PWO - Palletized without Cartons
AR2 - 2' Assymetrical Reflector		G20 - 20' Aircraft Cable w/ 12" Arms (2)				CD - Continuous Dimming (T8)
AR3 - 3' Assymetrical Reflector		NSWG2 - 2' Wire Guard For Strip				SD - Step Dimming (T8)
AR4 - 4' Assymetrical Reflector		NSWG3 - 3' Wire Guard For Strip				CD5 - Continuous Dimming (T5)
10JC - (3)S Hooks and 10' Jack Chain Set		NSWG4 - 4' Wire Guard For Strip				SD5 - Step Dimming (T5)
						WOC - 120/347 Volt Sensor
						WOC1 - 480 Volt Sensor
						C1 - 6' Cord w/120V Nema Plug 16/3 15A
						C2 - 6' Cord w/277V Nema Plug 16/3 15A
						C3 - 10' Cord w/277V Nema Plug 16/3 20A
						C4 - 6' Cord w/480V Nema Plug 16/3 20A
						WH34 - Wiring Harness 3-Wire 4-Foot
						WH44 - Wiring Harness 4-Wire 4-Foot

Energy Saving Tip!
Our Occupancy Sensor
option instantly turns
lights on and off