



Catalog Number	
Project	Type

Features & Specifications

Features

- Compact, low-profile design in neutral finish
- Universal mounting plate with EZ Quick Connect for fast installation
- UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

Electrical

- Dual 120V/277V voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- 6V, 4.5Ah, sealed lead acid, maintenance-free, rechargeable battery
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours

Mounting

- Surface mount via easy connect back plate, which fits most standard junction boxes and snaps into place making internal electrical connections
- Conduit mount using knockouts on back plate

Housing

- Injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in white or black finish

Illumination

- Two fully adjustable 5.4 watt, glare-free lighting heads
- High-performance smooth thermoplastic reflector and plastic lens for optimal light distribution


Warranty

- Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

R-1 SERIES EMERGENCY LIGHT



DIMENSIONS



Please contact your Horizon Sales Representative for more information.

Ordering Nomenclature

Ex: (MR-16 Emergency Light, White Housing = R-16W)

	R-1		
	SERIES R-1	HOUSING COLOR W - White B - Black	ACCESSORIES SD - Self Diagnostic CP - Cord and Plug NB - NiCad Battery K5 - 5.4W Krypton Lamps HT - Internal Heater