


TSS SERIES

Telescopic Staggered Strip



DESIGN

The TSS Series Telescopic Staggered Strip is adjustable to maintain a uniform distribution of light especially helpful in end of row applications. The fixture was designed specifically for coves or display cases where lighting is installed as a continuous run from end to end.

ACCESSORIES

Order as separate line item



6' 16/3 CORD W/ 15A
NEMA PLUG
C1 (120V)
C2 (277V)
C4 (480V)



WIRING HARNESS
WH34 (3 WIRE, 4')
WH44 (4 WIRE, 4')
WH54 (5 WIRE, 4')




T8 EMERGENCY BALLAST
EB5 (500 LUMEN)
EB7 (700 LUMEN)
EB14 (1400 LUMEN)
EB30 (3000 LUMEN)



MOTION SENSOR
WOC (120/277V)
WOC1 (347/480V)

PHOTOMETRICS

IES INDOOR REPORT
PHOTOMETRIC FILENAME: TSS232.IES
POLAR GRAPH



Maximum Candela = 1170 Located At Horizontal Angle = 90, Vertical Angle = 15
1 - Vertical Plane Through Horizontal Angles (0 - 270) (Through Max. Cd.)
2 - Horizontal Plane Through Vertical Angle (15) (Through Max. Cd.)

ORDERING INFORMATION

Description	Part Number
2L 14W T5 120/277V	TSS214D(A)
2L 17W T8 120/277V	TSS217D(A)
2L 21W T8 120/277V	TSS221D(A)
2L 24W T5HO 120/277V	TSS224D(A)
2L 25W T8 120/277V	TSS225D(A)
2L 28W T5 120/277V	TSS228T5D(A)
2L 32W T8 120/277V	TSS232D(A)
2L 39W T5HO 120/277V	TSS239D(A)
2L 54W T5HO 120/277V	TSS254D(A)

Option Codes

(A) Options

Blank - None
10RS - ≤10% THD, Rapid Start
P - Program Start
20 - ≤20% THD

MOUNTING

2 Sets of each mount must be ordered per fixture



(3)S HOOKS AND
CHAIN SET
10JC



TONG HANGER
THE (END MOUNT)
THS (SIDE MOUNT)



AIRCRAFT CABLE WITH
12" ARMS
G10 (10')
G12 (12')
G15 (15')

TECHNICAL INFORMATION

Fixture housing, lamp holder brackets, end sections, and channel cover are constructed of heavy gauge die-formed steel. Fully open, fixture stagger is as follows: 2' = 10", 3' = 20", 4' = 26". ETL listed. Suitable for damp locations. Ballasts are solid state electronic. Ballasts and lamp holders are replaceable without removing from ceiling. Can be mounted as single fixture or in a continuous row. All reflective surfaces are finished with a high reflectance, lighting fixture white polyester powder.