



LED Series Information

Features:

Heavy Duty Die Cast Aluminum Housing with a Textured Architectural Bronze Powdercoat Finish over a Chromate Conversion Coating for Durability

Injection Molded Polycarbonate Lens with UV Inhibitors

Housing Features Threaded 1/2" Coin Plugs with Gaskets for Conduit and/or Photo Cell Installation

Silicone Gasket Eliminates Moisture, Dust and Insect Penetration

CSA Listed for Wet Locations

Custom Colors Available

Applications:

- Residential Exteriors
- Entryways, Walkways,
- Stairways and Perimeters
- Parking Garages
- Wet Industrial Commercial Spaces

Accessories Sold Separately

Options:


LED 12" x 12" Medium Vandal Resistant



VN41L



Dimensions:




LED Series Order Information

Typical Ordering Number:
VN41L-2X15-Q-4-6-PC1

Model#	Total Watts	Ballast	Color Temp	Optics	Options
VN41L	2X7H =2x7.5w (15w)* 3X7H =3x7.5w (22.5w)* 4X7H =4x7.5w-350MA only (30w)* 2X15 =2x15w (30w)* *40 LPW (Lumens per watt)	Q = Quad Tap	2 = 2700k 3 = 3000k 4 = 4000k	N = None 2 = 20° 4 = 40° 6 = 60°	PC1 = 120V Photocell PC2 = 208-277V Photocell VN40IR = Internal Aluminum Reflector



Accessories



VN40IR



(PC1 & PC2) Photocell



Optic Options:
(2) 20° beam
(4) 40° beam
(6) 60° beam

LED Information

"GREEN" ENERGY EFFICIENCY:

Cost of ownership (life and efficacy advantages) - 2 year payback possible

Long life (50,000 hrs) – reliability, sustained image

No mercury or lead

FAST SHIPPING

Large Inventory of
LED MODULES & DRIVERS
IN STOCK

TECHNICAL:

Good quality white light (Ra 80+)

Choice of Color Temperatures (2700K, 3000K and 4000K)

50Hz-60Hz

Choice of operation: can be run as low as 350mA for maximum efficacy and up to 700mA for maximum output

Possibilities include: sharp beam cut-off optics, very low profile spot and flood optics (<20mm), and adjustable beam shaping

Minimal heat (IR) in the beam – can be placed close to merchandise

Fully dimmable (analog or digital)

Uniform beam (intensity and color temperature - no yellow ring or color shadows)

Color point consistency part to part and through life

Universal operating position

Extremely low UV- perfect for high value items sensitive to UV

Light Emitting Diode is fully enclosed, providing an IP 66 rating.